



## 605100502

Led Driver 0-40W 12V 3300mA DC Phase-Cut Constant Voltage Dimmable



### Accessories, Transformers & Drivers

#### General

|                          |             |
|--------------------------|-------------|
| Model                    | Static      |
| Suitable for outdoor use | No          |
| Dimmable                 | Yes         |
| Housing material         | Plastic     |
| Colour housing           | Satin black |
| Housing material         | Steel       |
| Driver lifetime          | 30.000 h    |
| Length                   | 137.00 mm   |
| Width                    | 82.00 mm    |
| Height                   | 31.00 mm    |
| Net weight               | 0.210 kg    |
| Warranty                 | 3 years     |

#### Dimming

|   |     |
|---|-----|
| Dimming 0-10 V                            | No  |
| Dimming 1-10 V                            | No  |
| Dimming D4i                               | No  |
| Dimming DALI                              | No  |
| Dimming DALI-2                            | No  |
| Dimming DSI                               | No  |
| Dimming DMX                               | No  |
| Dimming potentiometer (integrated)        | No  |
| Dimming LineSwitch                        | No  |
| Dimming manufacturer's proprietary system | No  |
| Dimming mains voltage modulation          | No  |
| Dimming phase cut-off                     | Yes |
| Dimming phase cut-on                      | Yes |
| Dimming programmable                      | No  |
| Dimming RF                                | No  |
| Dimming Sine Wave Reduction               | No  |
| Dimming Touch and Dim                     | No  |
| Dimming Zigbee                            | No  |
| Dimming with push-button                  | No  |
| Constant light output (CLO)               | No  |

#### Technical specifications

|  |            |
|--|------------|
| Suitable for constant current          | No         |
| Suitable for constant voltage          | Yes        |
| Output voltage                         | 12 V       |
| Output current                         | 3300 mA    |
| Suitable for DC-voltage (primary side) | Yes        |
| Output power                           | 0..39.6 W  |
| Input voltage                          | 220..240 V |
| Power consumption                      | 5.58 W     |
| Frequency input voltage                | 50-60 Hz   |
| Efficiency                             | 85%        |

|   |              |
|---|--------------|
| Independently operating                       | Yes          |
| PWM modulation                                | No           |
| Mains surge immunity (differential mode, L-N) | 1.0 kV       |
| Overload protection                           | Yes          |
| Emergency power supply system                 | None         |
| Overtemperature protection                    | No           |
| Ambient temperature                           | -40 .. 85 °C |
| Short-circuit protected                       | Yes          |
| Degree of protection                          | IP20         |
| Protection class                              | II           |

|                                  |    |
|----------------------------------|----|
| Operation by Bluetooth           | No |
| Compatible with Apple HomeKit    | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa     | No |
| Compatible with Casambi          | No |
| IFTTT support available          | No |

#### Ordering details

|                |                |               |
|----------------|----------------|---------------|
| 605100502      | Quantity (pcs) | EAN           |
| Single package | 1              | 8718739076341 |

